## according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

30332 Whittle Waxes Stain raw Article No.: Print date: 09.01.2020 Revision date: 16.07.2019

Page 1 / 8 Version: Issue date: 16.07.2019

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

product identifiers

Article No. (manufacturer/supplier) 30332

Identification of the substance or mixture Whittle Waxes Stain raw

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

paint

coating material

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

WHITTLEWAXES Pty Ltd.

P.O. Box 455 Cooroy Telephone: + 61 1300 326 929

QLD 4563

Australia info@whittlewaxes.com.au www.whittlewaxes.com.au

Dept. responsible for information:

+61 1300 326 929 Sale

info@whittlewaxes.com.au E-mail (competent person)

1.4. Emergency telephone number

+61 1300 326 929

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

#### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

**Hazard statements** 

not applicable

**Precautionary statements** 

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of the reach of children.

P103 Read label before use.

contains:

not applicable

Supplemental Hazard information (EU)

**EUH208** Contains Dodecanoic, cobalt salt. May produce an allergic reaction.

**FUH210** Safety data sheet available on request.

2.3. Other hazards

#### SECTION 3: Composition / information on ingredients

#### 3.2. Mixtures

Product description / chemical characterization

Description Solvent-borne paints

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. **REACH No.** CAS No. **Chemical name** INDEX No. classification: // Remark

Wt %

## according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

30332 Article No.: Print date: 09.01.2020

649-327-00-6

Version:

Whittle Waxes Stain raw Revision date: 16.07.2019 Issue date: 16.07.2019

ΕN Page 2 / 8

918-481-9 64742-48-9 hydrocarbons, C10-C13, n-alkane, iso-alkane, cyclic compound, < 2 % 50 - 100

01-2119457273-39

aromatics

Asp. Tox. 1 H304

245-018-1 01-2119979088-21

22464-99-9 2-ethylhexanoic acid, zirconium

< 0,5 Repr. 2 H361

#### Additional information

Full text of H-phrases: see section 16.

#### **SECTION 4: First aid measures**

#### Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

#### Indication of any immediate medical attention and special treatment needed

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

#### Extinguishing media which must not be used for safety reasons:

strong water jet

#### Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

#### 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

#### SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

#### **Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

#### Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

#### Reference to other sections

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

Article No.: 30332 Whittle Waxes Stain raw Print date: 09.01.2020 Revision date: 16.07.2019 Version: 25.0 Issue date: 16.07.2019

Observe protective provisions (see section 7 and 8).

#### **SECTION 7: Handling and storage**

Due to the content of organic solvents in the preparation:

#### 7.1. Precautions for safe handling

#### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

EN Page 3 / 8

#### Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

#### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

#### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### Occupational exposure limit values:

2-ethylhexanoic acid, zirconium

EC No. 245-018-1 / CAS No. 22464-99-9

TWA: 5 mg/m3 STEL: 10 mg/m3

#### **Additional information**

TWA: long-term occupational exposure limit value STEL: short-term occupational exposure limit value

Ceiling: peak limitation

#### DNEL:

2-ethylhexanoic acid, zirconium

EC No. 245-018-1 / CAS No. 22464-99-9

DNEL long-term dermal (systemic), Workers: 15,75 mg/kg

#### **PNEC**

2-ethylhexanoic acid, zirconium

EC No. 245-018-1 / CAS No. 22464-99-9

PNEC aquatic, freshwater: 0,36 mg/l

PNEC aquatic, marine water:

PNEC sediment, marine water:

#### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

#### Occupational exposure controls

#### according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

Whittle Waxes Stain raw 30332 Article No.: Print date: 09.01.2020 Revision date: 16.07.2019

ΕN Page 4 / 8 Version: Issue date: 16.07.2019

#### Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

#### Hand protection

For prolonged or repeated handling the following glove material must be used: e.g. Nitrile (according to DIN EN 374)

Thickness of the glove material > 0,4 mm; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Eye protection

Wear closely fitting protective glasses in case of splashes.

#### Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

#### **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

#### **SECTION 9: Physical and chemical properties**

#### Information on basic physical and chemical properties

Appearance:

Physical state: Liauid Colour: refer to label Odour: characteristic Odour threshold: not applicable pH at 20 °C:: not applicable Melting point/freezing point: not applicable

Initial boiling point and boiling range:

Method: DIN 53171

Source: Terpene hydrocarbons, by-products

Flash point: > 61 °C **Evaporation rate:** not applicable

Flammability (solid, gas):

Burning time (s): not applicable

Upper/lower flammability or explosive limits:

0,6 Vol-% Lower explosion limit:

Method: calculated

Source: hydrocarbons, C10-C13, n-alkane, iso-alkane, cyclic compound, <

2 % aromatics

7 Vol-% **Upper explosion limit:** 

Method: calculated

Source: hydrocarbons, C10-C13, n-alkane, iso-alkane, cyclic compound, <

2 % aromatics

Vapour pressure at 20 °C:: not applicable Vapour density: not applicable

Relative density:

Density at 20 °C:: 0,865 g/cm<sup>3</sup>

Method: DIN 53217

Solubility(ies):

Water solubility (g/L) at 20 °C:: insoluble Partition coefficient: n-octanol/water: see section 12

240 °C Auto-ignition temperature:

## according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

Article No.: 30332 Whittle Waxes Stain raw Print date: 09.01.2020 Revision date: 16.07.2019 Version: 25.0 Issue date: 16.07.2019

Method: calculated

Source: hydrocarbons, C10-C13, n-alkane, iso-alkane, cyclic compound, <

EN Page 5 / 8

2 % aromatics

Decomposition temperature: not applicable Viscosity at 40 °C:: 24,68 mm²/s

Method: kinematisch

Explosive properties: not applicable
Oxidising properties: not applicable

9.2. Other information

Solid content (%): 37 Wt %

solvent content:

Organic solvents: 62 Wt % Water: 0 Wt %

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

#### 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

#### 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

#### 10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

#### **SECTION 11: Toxicological information**

Classification according to Regulation (EC) No 1272/2008 [CLP] No data on preparation itself available.

#### 11.1. Information on toxicological effects

#### **Acute toxicity**

hydrocarbons, C10-C13, n-alkane, iso-alkane, cyclic compound, < 2 % aromatics inhalative (vapours), LC50, Rat: > 20 mg/l (4 h)

#### skin corrosion/irritation; Serious eye damage/eye irritation

Toxicological data are not available.

#### Respiratory or skin sensitisation

Toxicological data are not available.

#### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

2-ethylhexanoic acid, zirconium

Reproductive toxicity

#### Specific target organ toxicity

Toxicological data are not available.

#### Aspiration hazard

Toxicological data are not available.

#### Practical experience/human evidence

#### Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

Article No.: 30332 Whittle Waxes Stain raw Print date: 09.01.2020 Revision date: 16.07.2019 Version: 25.0 Issue date: 16.07.2019

natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

ΕN

Page 6 / 8

#### **Overall Assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

#### **SECTION 12: Ecological information**

#### overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

#### 12.1. Toxicity

hydrocarbons, C10-C13, n-alkane, iso-alkane, cyclic compound, < 2 % aromatics

Fish toxicity, LC50: > 1000 mg/l (96 h) Daphnia toxicity, EC50: > 1000 mg/l (48 h) Algae toxicity, ErC50: > 1000 mg/l

#### Long-term Ecotoxicity

Toxicological data are not available.

#### 12.2. Persistence and degradability

Toxicological data are not available.

#### 12.3. Bioaccumulative potential

Toxicological data are not available.

#### **Bioconcentration factor (BCF)**

Toxicological data are not available.

#### 12.4. Mobility in soil

Toxicological data are not available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Appropriate disposal / Product

#### Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

#### List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 080111

#### packaging

#### Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

#### **SECTION 14: Transport information**

No dangerous good in sense of this transport regulation.

## 14.1. UN number

not applicable

#### 14.2. UN proper shipping name

#### 14.3. Transport hazard class(es)

not applicable

#### 14.4. Packing group

not applicable

#### 14.5. Environmental hazards

Land transport (ADR/RID) not applicable

## according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

Article No.: 30332 Whittle Waxes Stain raw Print date: 09.01.2020 Revision date: 16.07.2019 Version: 25.0 Issue date: 16.07.2019

Marine pollutant not applicable

#### 14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

EN Page 7 / 8

Advices on safe handling: see parts 6 - 8

#### **Further information**

#### Land transport (ADR/RID)

tunnel restriction code

Sea transport (IMDG)

EmS-No. not applicable

Air transport (ICAO-TI / IATA-DGR)

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

#### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** legislation

#### Directive 2010/75/EU on industrial emissions

VOC-value (in g/L): 542

#### Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/f); VOC limit value: 700 g/l

Maximum VOC content (g/L) of the product in a ready to use condition: 542

#### **National regulations**

#### **Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

#### 15.2. Chemical Safety Assessment

#### For the following substances of this preparation a chemical safety assessment has been carried out:

EC No. CAS No.	Chemical name	REACH No.
918-481-9 64742-48-9	hydrocarbons, C10-C13, n-alkane, iso-alkane, cyclic compound, < 2 % aromatics	01-2119457273-39
245-018-1 22464-99-9	2-ethylhexanoic acid, zirconium	01-2119979088-21

#### **SECTION 16: Other information**

#### Full text of classification in section 3:

Asp. Tox. 1 / H304 Aspiration hazard Repr. 2 / H361 Reproductive toxicity

May be fatal if swallowed and enters airways. Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).

#### Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

#### **Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

# Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

Article No.: Print date: Version: 30332 09.01.2020 25.0 Whittle Waxes Stain raw Revision date: 16.07.2019 Issue date: 16.07.2019

EN Page 8 / 8