## The Importance of Fit

## 3M™ Half Face Respirator 6000 Series

Respiratory Protection is only effective if it is correctly selected, fitted and worn throughout the time when the wearer is exposed to respiratory contaminants. Before assigning any respirator to be worn in a contaminated area, it is recommended to perform a face fit check before entering the workplace.

## These fitting instructions must be followed each time the respirator is worn.

Be Clean Shaven: Do not use with beards or other facial hair that prevent a good seal between the face and the face seal of the respirator.



Place the respirator over the mouth and nose. Pull the head harness over the crown of the head



Hook the bottom straps together behind your neck.



Tighten the top & bottom straps to create a secure fit. Do not over-tighten.



Place the palm of your hand over the exhalation valve cover and exhale gently. If the facepiece bulges slightly and no air leaks are detected between the face and the facepiece, a proper seal has been obtained.

## **Negative Pressure Face Fit Check**



With cartridges:
Place the palms of

Place the palms of your hands over the cartridges to restrict the air flow. Inhale gently. The facepiece should collapse slightly.



With Particulate Filters – Disc Style:

Place your thumbs onto the centre portion of the filters to restrict the air flow. Inhale gently. The facepiece should collapse slightly.



With Solid-top Particulate Filters:

Squeeze filter covers together using the palms of your hands and fingers to restrict airflow. Inhale gently. The facepiece should collapse slightly.

If air leaks between the face and the faceseal of the respirator, reposition it and adjust the straps for a tighter seal. Repeat steps 4 and 5. If you cannot achieve a proper fit, DO NOT enter the hazardous area. Consult your supervisor.

Warning: Respirators must not be used until your employer has determined whether usage will be in accordance with manufacturer's instructions. The wearer must be trained in the proper fitting and use of this product. Failure to follow all instructions and warnings on the use of this product and/or failure to wear this respirator during all times of exposure can reduce respirator effectiveness and result in illness or death. All respirators should be used in accordance with Australian Standard AS/NZS 1715. It is recommended that fit testing be conducted before assigning a respirator to an individual. If you cannot achieve a proper fit, do not enter contaminated areas. Do not use with beards or other facial hair or conditions that prevent a good seal between the face and the sealing surface of the respirator.

3M Australia Pty Ltd
Personal Safety Division
Bldg A, 1 Rivett Road
North Ryde NSW 2113
TechAssist Helpline: 1800 024 464
Customer Service: 1300 363 565
Email: techassist@mmm.com
Web: www.3M.com/au/ppesafety

3M New Zealand Ltd
Personal Safety Division
94 Apollo Drive, Rosedale
Auckland 0632
TechAssist Helpline: 0800 364 357
Customer Service: 0800 252 627
Email: techassist@mmm.com
Web: www.3M.com/nz/ppesafety